

SANYO

PLC-XR70N

True XGA Compressed SXGA, EWS Multimedia Projector



- True XGA (1024 x 768)/Compressed SXGA/DVD/Electronic Workstation (EWS) Multimedia Projector
- 70" (Dia.) Large-Screen, Rear Projection
- 250 NIT
- Over 85% Uniformity
- Three 1.3" TFT Polysilicon LCD Panels
- 120W UHP Lamp
- Proprietary Digital Realized Interpolation Technology (DRIT) — Elegant Compression
- Auto Image Feature
- Intuitive Graphic User Interface (GUI) On-screen Menus
- Revolutionary Polarized Beam Splitter (PBS) Optical System
- Proprietary HQVF Video Circuit for Superior Video Image
- Component Video Inputs
- Three PC Input Terminals
- International Capability: Multivoltage, Multilanguage, Four Color System



PLC-XR70N True-XGA Multimedia Projector

Other Features:

- Graphic User Interface (GUI) On-Screen Menus
- Polarized Beam Splitter (PBS) Optical System
- High Quality Video Frequency Video Circuit
- Component Video Inputs
- International Capability: Multivoltage, Multilanguage Displays, and Four Color System
- Track Pad Wired and Infrared Remote Control

PLC - XR 7 0 N

S P E C I F I C A T I O N S

Type	XGA (1024 x 768 Dots) Multimedia
Brightness	250 NIT
Uniformity	Over 85%
LCD Panel System	1.3" TFT (Thin Film Transistor) Polysilicon x 3
Number of Pixels	2,359,296
Contrast Ratio	100:1
Project Method	One Lens, One-Miller Reflection
Projection Lens	f23.7; F2.5"
Projection Image (Dia.)	70"
Field of Angle Views	H: +/- 40°, V: +/- 15°; 1/3 Brightness
Aspect Ratio	4:3
Projection Lamp	120 Watt Ultra High Power
Scanning Frequency	H Sync: 15-80kHz V Sync: 50-100Hz
Over Scan (Video Mode)	4% H; 3% V
Dot Clock	135MHz
Color System	PAL/SECAM/NTSC/NTSC4.43
Computer Compatibility	SXGA/XGA/SVGA/VGA/MAC/PC98
Input Terminal (PC)	D-Sub 15 Pin x 3; Multipole-Control Port x 3; Stereo Minijack x 3
Input Terminal Video (Audio)	Composite Video Y, B-Y, R-Y x 2 RCA; (L/R (RCA) x 2) Composite Video BNC x 1 RCA x 1; (L/R (RCA) x 1) Separate Y/C (Din 4 Pin) x 3
PC Terminal	Mouse/Keyboard x 3 (Mini Din 6 Pin x 2, Mini Din 4 Pin x 1)
Sound Output	10-Watt Stereo
Voltage	100-120 Volt or 200-240 Volt AC, 50/60Hz
Power Consumption	210 Watts
Dimensions (WxHxD)	59.9" x 78.8" x 29.5"
Net Weight	220 Pounds
Warranty	3 Years Parts and Labor; 90 Days Lamp

Because its products are subject to continuous improvements, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

Presentation Technologies
21605 Plummer St.
Chatsworth, CA 91311
Phone: (818) 998-7322, ext. 288
Fax: (818) 717-2719
www.sanyolcd.com
©1998 SANYO Presentation Technologies