

Overhead Projectors

HP-3K

Portable overhead projector

ELMO's self-contained portable overhead series combines outstanding design with powerful and brilliant screen performance.



Aperture size	254X254 mm (10x10 in)
Carrying handle	Provided
Dimensions	Folded 463X384X129 mm (18.2X15.1X5.1 in) Assembled 463X384X725 mm (18.2X15.1X28.5 in)
Forced air cooling	Built-in
High/normal lamp switch	Provided
Image size	0.89~2.54 m (2.9~8.3 ft)
Light output	3,000 lumen
Magnification	X3.5 ~X10.0 x3.5 ~X10.0
Pen tray	Provided
Power cord	3 m (9.8 ft) permanently attached
Power Source	AC single phase 120V
Projected material	Transparency and roll
Projection distance	1.2~3.1 m (3.9~10.2 ft)
Projection lamp	ANSI: ENX 82V-360W or ENX-5 86V-360W
Projection lens	290 mm (11.4 in) 1 element
Safety interlock switch	Built-in safety interlock switch cuts off power when stage frame is opened
Safety thermal cut-off switch	Built-in safety thermal cut-off switch automatically cuts off power to lamp if projector overheats.
Spare lamp holder	Provided
Tilting angle adjustment	Up to 20
Weight	7.9 kgs (17.4 lbs)
Writing roll attachment	Optional accessory