

## **Overhead Projectors**

## HP-3K DX

## Portable overhead projector

ELMO's self-contained portable overhead series combines outstanding design with powerful and brilliant screen performance.



**Power cord** 3m (9.8 ft) permanently attached

**Tilting angle adjustment** Up to 20

**Aperture size** 254X254 mm (10X10 in)

**Carrying handle** Provided

**Dimensions** Folded 463X384X129 mm (18.2X15.1X5.1 in)

Assembled 463X384X725 mm (18.2X15.1X28.5 in)

Forced air cooling Built-in
High/Normal lamp switch Provided

**Image size**  $0.89 \sim 2.54 \text{ m} (2.9 \sim 8.3 \text{ ft})$ 

**Light output** 3,000 lumen **Magnification** X3.5~X10.0

Pen tray Provided

**Power source** AC single phase 120V

**Projected lamp** ANSI: ENX 82V-360W or ENX-5 86V-360W **Projected material** ANSI: ENX 82V-360W or ENX-5 86V-360W

**Projection distance**  $1.2 \sim 3.1 \text{ m} (3.9 \sim 10.2 \text{ ft})$ 

**Projection lens** 290 mm (11.4 in)

1-element

Quick lamp change device Provided

**Safety interlock switch** Built-in safety interlock switch cuts off power when stage frame is opened.

Safety thermal cut-off switch Built-in safety thermal cut-off switch automatically cuts off power to lamp is projector

overheats.

**Weight** 8.0 kgs (17.6 lbs)

Writing roll attachment Optional accessory