

ELMO

Overhead Projectors

HP-2850 SOLAR

High performance portable overhead projector

The latest in high performance portable overhead technology. Portability and high light output for the most effective LCD presentations.



Aperture size	285 x 285mm (11.2 x 11.2in)
Dimensions	Folded: 129x523x384mm (5.1x20.6x15.1in) Assembled: 705x523x384mm (27.8x20.6x15.1in) Folded: 129x523x384mm (5.1x20.6x15.1in)
Forced air cooling	Built-in
High/Low lamp switch	Provided
Image size	1.00 to 3.00m (3.3 to 9.8ft)
Light output	Over 5,000 lumens
Magnification	x3.5 to x10.5
Pen tray	Provided
Power source	AC single phase 50/60Hz
Projected material	Transparency, writing roll & LCD panel
Projected material	Transparency, writing roll & LCD panel
Projection distance	1.26 to 3.74m (4.1 to 12.3 ft)
Projection lamp	400W Metal Halide lamp
Projection lens	289 - 330mm (11.4 - 13.0 in) 3-element (variable focal type)
Safety interlock switch	Built-in safety interlock switch cuts off power when stage frame is opened
Safety thermal cut-off switch	Built-in safety cut-off switch automatically cuts off power to lamp if projector overheats
Tilting angle adjustment	Up to 20
Weight	10.5kgs (23.2lbs)
Writing roll attachment	Optional accessory