

ELMO

Color Monitors

1432NSA

13 inch color monitor

Economical high-performance color CCTV monitor.



Audio speaker	3" (8 cm) round, 1 W output
Audio Terminals	RCA pin x4 for input A and input B channels, bridged-out possible
Color System	NTSC/PAL Auto Select
Color Temperature	6,500 K
CRT	13" (diagonally measured) in-line guns, stripe pitch of 0.64mm
Dimensions	14-1/2" W x 12-1/4" H x 14-11/16"D
Horizontal	320 TV lines (NTSC)
Power Consumption	0/87A
Power requirements	120V AC, 50/60 Hz
Scanning Frequency	H 15.625 kHz (PAL) 15.75 kHz (NTSC) V 50/60 Hz H 15.625 kHz (PAL) 15.75 kHz (NTSC)
Weight	21 lbs. (9.6 kg)
Y/C	Y: 1.0V (p-p), 75 ohms, negative sync. C: 0.3V (p-p), 75 ohms (PAL) 0.286 V (p-p) 75 ohms (NTSC)

INPUT TERMINALS

Input A: Composite Video	1.0V (p-p) 75 ohms, negative sync, auto termination BNC x2 bridge-out possible
Input B: Composite Video	1.0 V (p-p) 75 ohms, negative sync, auto termination BNC x2 bridge-out possible