

## **Black & White Security Cameras**

## TSE270X

## **CCD black & white video camera**

Budget-priced 1/3" CCD black & white camera. Features low light sensitivity, backlight compensation, automatic electronic shutter and external adjustments for eazy installations.



Accumulation mode	Field
AES(Automativ Electronic Shutter)	Provided (Factory-set at OFF)
AES(Automative Electronic Shutter)	Provided (Factory-set at OFF)
AGC	Built-in
Ambient humidity	30%~90%
Ambient temperature	-10 C~50 C(14F~122F)
Auto-iris terminal	4P square connecter (DC/Video)
<b>Backlight</b> compensation	Provided (Factory-set at OFF)
Dimensions	60(W)x60(H)x120(D)mm (2.4x2.4x4.7in)
<b>Effective picture element</b>	512(H)x492(V)
Gamma correction	0.45
Lens mount	CS
<b>Minimum illumination</b>	0.09IX (F1.4 under incandescent lamp, w/SENS-up on)
Output signal	VBS 1.0p-p 75, EIA, compatible
Pick-up device	1/3" Black & White Interline-Transfer CCD
Power	AC24V 10% 60Hz 1Hz
Power consumption	Approx. 6W
Power terminal	3P screw terminal
Resolution	380 TV(H)lines,350TV(V) lines
S/N ratio	More than 46dB
Scanning area	4.92mm(H)x3.69mm(V)
Scanning frequency	15.75kHz(H), 60Hz(V)
Scanning system	2:1 interlaced
Scanning systme	2:1 interlaced
Sens-up	Provided (Factory-set at OFF)
Sync. system	Line-lock
Weight	510g(1.12 lbs)