

Black & White Security Cameras

TSE271X

CCD black & white video camera

Budget-priced 1/3" CCD black & white camera. Features low light sensitivity, backlight compensation, automatic electronic shutter and external adjustments for eazy installations.



Accumulation mode	Field
AES (Automatic Electronic Shutter	Provided (Factory-set at OFF)
AGC	Built-in
Ambient humidity	30%~90%
Ambient temperature	-10 C~50C(14F~122F)
Auto-iris terminal	4P square connector (DC/Video)
Backlight compensation	Provided (Factory-set at OFF)
Dimensions	60(W)x60(H)x120(D)mm (2.4x2.4.4.7in)
Effective picture element	512 (H)x492(V)
Gamma correction	0.45
Lens mount	CS
Minimum illumination	0.09Ix (F1.4 under incandescent lamp, w/Sens-up on)
Output signal	VBS 1.0Vp-p, 75, EIA, compatible
Pick-up device	1/3" Black & White Interline-Transfer CCD
Power	DC12V(DC11V-16V)
Power consumption	Approx. 3.2W
Power terminal	2P screw terminal
Resolution	380TV(H) lines, 350TV(V)lines
S/N ratio	More than 46dB
Scanning area	4.92mm(H)x3.69mm(V)
Scanning frequency	15.73kHz(H), 59.94Hz(V)
Scanning system	2:1 interlaced
Sens-up	Provided (Factory-set at OFF)
Sync system	Internal
Weight	320g (0.71 lbs)