

Black & White Security Cameras

TSE272X

CCD black & white video camera

Budget-priced 1/3" CCD black & white camera. Features low light sensitivity, backlight compensation, automatic electronic shutter and external adjustments for eazy installations.



Accumulation mode Field

AES (Automation Electronic Shutter Provided (Factory-set at OFF)

AGC Built-in

Ambient humidity 30%~90%

Ambient temperature $-10 \text{ C} \sim 50\text{C} (14\text{F} \sim 122\text{F})$

Auto-iris terminal 4P square connector (DC/Video)

Power cord

Backlight compensation Provided (Factory-set at OFF)

Dimensions 60(W)x60(H)x120(D)mm (2.4x2.4x4.7in)

Effective picture element 512(H)x492(V)

Gamma correction 0.45

Lens mount CS

Minimum illumination 0.09 Ix (F1.4 under incandescent lamp, w/Sens-up on)

Output VBS 1.0Vp-p, &%, EIA, compatible

Pick-up device 1/3" Black & White Interline-transfer CCD

Power AC 120 10%60Hz 1Hz

Power consumption Approx. 6W

Power terminal Power cord

Resolution 380TV(H) lines, 350TV(V) lines

S/N ratio More than 46dB

Scanning area 4.92mm(H)x3.69mm(V)

Scanning Frequency 15.75kHz(H), 60Hz (V)

15.73kHz(H), 59.94Hz (V)

Scanning system 2:1 interlaced

Sens-up Provided (Factory-set at OFF)

Sync. system Line-lock

Weight 600g(1.32 lbs)