

SPECIFICATIONS COLORPLEX-16 MULTIPLEXER

Camera Type	B/W & Color Applicable	Camera Type	B/W & Color Applicable
Video Input		VCR Synchronization	
Camera Input	1 V p-p, 75 Ω x 16	Programmable Filed Delay	Yes
VCR Input	1 V p-p, 75 Ω x 1	Switching Pulse Input	Yes
S-VHS Terminal Input	Y: 1.0 V p-p, 75 Ω, C: 0.286 V p-p, 75 Ω	VCR Speed Auto Detection	Yes
Video Output		Priority Recording for	Yes
Main monitor	1 V p-p, 75 Ω x 1	Sensor-activated Channel	
Call monitor	1 V p-p, 75 Ω x 1	Motion Detection	Yes
Loop Through Out	1 V p-p, 75 Ω x 16	Key Lock	Yes
VCR Output	1 V p-p, 75 Ω x 1	Power Consumption	12 VDC, 20 W
S-VHS Terminal Output	Y: 1.0 V p-p, 75 Ω, C: 0.286 V p-p, 75 Ω	Dimensions (H,W,D)	1.75" x 17" x 7.9"
Relay Output	3	Weight	8.33 lbs
Resolution	910 x 512 (NTSC) / 910 x 612 (PAL)	Operating Temperature	32° to 122° F
Number of Color	16.7 Million/pixel	Power Adapter	AC 100V~240 V in, DC 12 V out
Time/Date	Yes	19" Rack Mountable	Yes
Camera Title	Yes	Rack Mounting Kit	Optional
Covert Camera	Yes	Remote Control	Optional
2 X Zoom	Yes	Duplex Operation	Yes
Adjustable Dwell Time	01 to 99 Seconds	Sensor Type	N.O or N.C.
Built-in Buzzer	Yes	Number of Alarm Input	16
RS-232 Port	Yes	VCR Record Time	2-999 hrs NTSC (3-999 hrs PAL)



ELMO

ELMO Mfg. Corp.
 1478 Old Country Road
 Plainview, NY 11803-5034
 Tel. 516-501-1400 Fax. 516-501-0429
 E-mail: elmo@elmousa.com
 Web: <http://www.elmousa.com>

ELMO Canada Mfg. Corp.
 44 West Drive, Brampton,
 Ontario, L6T 3T6
 Canada
 Tel. 905-453-7880 Fax. 905-453-2391
 E-mail: elmo.canada@cimtegration.com

Distributed by: